

DRYWALL PARTITIONING



WHAT IS RHINOBOARD® DRYWALL PARTITIONING?

The RhinoBoard® drywall solution is a high performance light-weight partition system consisting of a Gypframe® steel framework encased with RhinoBoard® gypsum plasterboards on either side. The joints are then taped and finished with RhinoGlide® gypsum jointing compound or RhinoLite® MultiPurpose® plaster.


Our RhinoBoard® 12.5 mm drywall solution gives you the advantage of a lightweight, but durable drywall system. Suitable for internal use, the flexible plasterboard complements a wide range of wall-types and finishes to give you peace of mind through long-term performance.



Build it


SAINT-GOBAIN

INSTALL A DRYWALL IN 5 EASY STEPS WITH GYPROC:



STEP 1: Install the Gypframe UltraSTEEL® wall frame.

STEP 2: Insulate the wall with Isover CavityBatt®.

STEP 3: Fix the RhinoBoard® 12.5 mm onto the Gypframe UltraSTEEL® framework using Gyproc 25 mm sharp point screws.

STEP 4 (a): Reinforce the joints with RhinoTape® and apply RhinoGlide® onto the tapered edges and butt joints for a final finish.



STEP 4 (b): Use RhinoLite® Multipurpose® (Inland) or RhinoLite® Natural Plus® (Coastal) for a full flush plastered finish. Paint the wall and finish it off with either RhinoCove Cornice® or Quickcornice®.



Scan the QR code to watch the installation videos!



BENEFITS OF DRYWALL:



SPEED OF INSTALLATION

3 to 4 times faster than masonry construction



LIGHT WEIGHT

8 to 10 times lighter than masonry systems



AESTHETIC APPEAL

Seamless and crack free surfaces, allowing ease of decoration via paint, tiles or wall papers



VERSATILITY

The systems enable use in all internal areas of your home and commercial areas



DRY CONSTRUCTION

Clean and dust free work environment



FLEXIBILITY

In creating and dividing spaces according to your needs



EXCELLENT PERFORMANCE

In terms of fire protection and sound insulation



ENVIRONMENT FRIENDLY

Green product which is recyclable and is made of environment friendly material

INSTALL A DRY WALL IN 5 EASY STEPS WITH GYPROC:



Install your drywall using RhinoBoard® 12.5 mm.



Step 1: Install the Gypframe® UltraSTEEL® wall frame.



Step 2: Insulate the wall with Isover CavityBatt®.



Step 3: Fix the RhinoBoard® 12.5 mm onto the Gypframe® UltraSTEEL® framework using Gyproc 25 mm sharp point screws.



Step 4 (a): Reinforce the joints with RhinoTape® and apply RhinoGlide® onto the tapered edges and butt joints for a final finish.



Step 4 (b): Use RhinoLite® Multipurpose® (Inland) or RhinoLite® Natural Plus® (Coastal) for a full flush plastered finish. Paint the wall and finish it off with either RhinoCove Cornice® or Quickcornice®.



Scan the QR code to watch the installation videos!



Gyproc
SAINT-GOBAIN

SAINT-GOBAIN